



Industrial Mobile Computer

RT40

- Qualcomm Octa-core high-efficiency processor and cutting-edge Android Q operating system, gives you unparalleled performance.
- 29 keys island-style keyboard + 4” giant touch screen, intuitive operation reaction, accurate even with glove hands.
- Built-in industrial-leading scan engine, captures 1D/2D barcodes on screen and paper even if they are contaminated, wrinkled or distorted. 15m long-range version is optional.



IP68 Waterproof
1.8m Drop Resistance



Seamless WiFi Roaming
4G Communication



13M Pixel
AF Camera



4” Touch Screen
Corning Gorilla glass



UEE UROVO
Enterprise Enabler




RT40 Industrial Mobile Computer




Specifications

 **Processor**
Octa-core 1.8GHz

 **O.S.**
Android Q (10)

 **Memory**
3GB RAM/ 32GB ROM,
4GB RAM/ 64GB ROM (optional)
microSD card,
Max.128GB extension.

 **Screen**
4 inch 480*800 pixel


 **Dimensions**
199 x 58(handle) x29(thinnest) mm
(78.34 x 22.83 x 11.41 in)

 **Cover glass**
Corning Gorilla

 **Weight**
425g


 **Main battery**
3.85V 5,200mAh


 **Audio**
Earpiece, speaker,
microphone Support PTT
(Push-to-Talk),
speaker loudness over
100dB at 10cm.


 **Scanner**
Standard range scanner and
extended range scanner are optional
Support all industry-leading 1D/2D
barcode on paper or screen


 **Camera**
Rear camera: 13M pixel
with flashlight.
(Not supported for
pistol grip version).

 **Buttons**
29 keys isolation keyboard

 **Bluetooth**
Bluetooth 5.0
BR/EDR
BLE


 **Wi-Fi**
802.11 a/b/g/n/ac/d/e/
h/i/k/r/v/w 2.4GHz/5GHz


 **Sensor**
Light sensor,
proximity sensor,
Accelerometer (optional),
e- compass (optional),
gyro sensor (optional).

 **Slot**
Nano SIM*1,
PSAM/ SIM*1
(self-adaption).

 **WWAN**
4G, 3G, 2G

 **GNSS**
GPS, Beidou,
GLONASS, Galileo.

 **Sealing**
IP68,
1.8m (5.9 ft.) flat concrete.

 **Environment**
Working temperature:-20 ~ +50°C
Storage temperature:-40 ~ +70°C
(-40°F ~ +158°F), Humidity:5%RH~95%RH
(non-condensing), ESD:±15kV air,
±8kV direct.

Urovo Technology Co., Ltd.

• Tel: 86 755-22673926 • Website: en.urovo.com • E-mail: urovo@urovo.com
• Address: Room 613,6/F.,Asia Trade Centre,79 Lei Muk Road,Kwai Chung,N.T.,Hong Kong

* This page is subject to change
without prior notice