



POS335


Product Overview


Designed with customer engagement at its core, the POS335 brings together the latest advancements in point of sale technology to create a highly versatile and affordable POS system.


Featuring a fanless J1900 processor, the POS335 delivers industry-leading reliability and efficiency, whilst ensuring diverse operating requirements are met. The highly responsive, long-life 15" PCAP touchscreen also ensures a smooth user experience, regardless of environment or application.


Its slim form factor facilitates a range of possible mounting options, which enables users to operate the system in a wide range of profiles. The design of the POS335 also allows for a range of integrated touch and non-touch secondary display options, ideal for customer information and point of sale marketing requirements, as well as an array of integrated peripherals.


Features

- 

Fanless Intel J1900 processor
- 

Highly responsive, long-life 15" PCAP touchscreen
- 

Range of integrated secondary display and peripheral options
- 

Support for a wide range of Windows Operating Systems
- 

Flexible, dual-hinge stand and a range of mounting options

Technical Specification

Model		POS335
Motherboard	Processor	Intel Celeron J1900 (Baytrail)
	RAM	4GB
	Storage	64GB SSD
Touch Panel	Graphic Engine	Intel HD Graphic DX11 and OCL 1.1
	Screen Size/Type	15" LED
	Touch Screen	P-CAP
	Brightness	>250 nits
	Resolution	1024 x 768
Expansion	Mini PCI-E Socket	1
I/O Ports	USB	1 x USB3.0, 4 x USB2.0
	Powered USB	3 x RJ45 Serial (Powered RS232)
	Serial	
	LAN	1 x RJ45 LAN
	Cash Drawer	1 x RJ11 Cash Drawer
Audio	Video	1 x DB15 VGA
	DC Jack	1 x 4 pin w/lock DC Jack
	Internal Speaker	2 x 2W (Optional)
Power	Power Adapter	120W/19V
Peripherals (Optional)	MSR	3-Track MSR (USB)
	Button	iButton (USB)
	Fingerprint	Fingerprint Reader (USB)
	2nd Display	8.4" non-touch or 8.4" P-CAP touch
	Customer Display	2 x 20 LCM Display (USB)
Certificate	EMC & Safety	FCC Class A, CE Mark, LVD
Environment	Operating Temperature	0°C ~ 35°C (32°F ~ 95°F)
	Storage Temperature	-20°C ~ 60°C (-4°F ~ 140°F)
	Humidity	20% ~ 80% RH non-condensing
Chassis	Material	Plastic
Weight and Dimensions	Weight (kg)	5kg (11lbs)
	Dimensions (W x H x D)	360 x 277 x 203mm (14.2" x 10.9" x 8.0")
Mounting	VESA Type	VESA Mount 100 x 100
Stands	Stand Options	Fixed Stand
Operating Systems	Supported OS	All variants of: Windows 7, Windows 8, 1, Windows 10 Linux



Features and Accessories



Customer Engagement Specialists